

# Roll-O-Mat®

## HIGH QUALITY ROLL FILTER MEDIA

### Features and Benefits

- ISO 16890: Coarse 35%
- Available in 4 widths
- Suitable for AAF installations

### Applications

Roll-O-Mat media has been developed for use in the AAF automatic roll filter, called Roll-O-Matic.



### Configurations

<b>Filter media</b>	Glass fibre
<b>Nominal thickness</b>	50 mm / 2"
<b>Initial pressure drop @ 2,5 m/s</b>	40 Pa
<b>Max. Operating Temperature</b>	80 °C
<b>Recom. final pressure drop</b>	Subject to optimization of lifecycle costs, max 130 Pa
<b>Recom. airflow range</b>	75% - 125% (of nominal airflow)
<b>Moisture resistance</b>	100% relative humidity

### Sizes

Roll-O-Mat rolls are available in 4 widths, suitable for AAF Roll-O-Matic installations.

Size	Width Mandrel (m)	Width Media (m)	Length of Roll (m)
3	0,830	~0,9	20
4	1,135	~1,2	20
5	1,439	~1,5	20
6	1,744	~1,8	20

\* For other manufactures' roll filter, please contact the AAF Sales office

Roll-O-Mat® is a registered trademark of AAF International in the U.S. and other countries.



Bringing clean air to life:

**AAF International**  
European Headquarters  
Odenwaldstrasse 4, 64646 Heppenheim  
Tel: +49 (0)6252 69977-0  
aafintl.com

Specifications and performance data contain average values within existing production specification tolerances and are subject to change without prior notice. AAF explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this information.

©2019 AAF International and its affiliated companies.  
PR\_105\_EN\_122019